

## Compact Model (25 ft<sup>3</sup>)

### Interior finish:

22 gauge stainless steel

### Exterior finish:

Sprayed enamel over steel

### STANDARD OPTIONS:

- Additional Access Ports
- Chart Recorders
- Condensate Removal Options
- Dry Air Tower
- Desiccant Drier
- Interior Receptacle
- International Construction 50 hz/CE (ILO 60 hz standard)
- Electrofin Coil Coating
- Glass Doors
- Interior Lighting
- Mechanical Covers
- Water Cooled Condensing Units



### OTHER CHAMBER OFFERINGS:

- CO2 Control
- Clean Room Flush Mount Chambers
- Pass-Thru Chambers
- Programmable Ramping / Freeze Thaw
- Remote Condensing Units

 **Environmental  
Specialties**  
An EMCOR Company

[www.eschambers.com](http://www.eschambers.com)

4412 Tryon Road  
Raleigh, NC 27606

t 919.829.9300  
f 919.833.9476

**Infinitely  
Precise.  
Ultimately  
Reliable.**

Model	Interior volume	Temp range	Humidity range	Volumetric uniformity	4-wire electrical volts/Ø/Amps	Int. dimensions WxDxH	Ext. dimensions WxDxH	Shelves Std/max	Weight LBS/KG
-------	-----------------	------------	----------------	-----------------------	--------------------------------	-----------------------	-----------------------	-----------------	---------------

**TEMP ONLY:**

A-C	25.2 ft <sup>3</sup> (714 liters)	35 to 70 °C	N/A	±0.3 °C	208-230 / 1 / 30	34 x 28.5 x 45 in. (87 x 73 x 114 cm)	41 x 34.5 x 76.5 in. (104 x 88 x 194 cm)	4/14	425/193
C-C		2 to 70 °C	N/A						675/306

**TEMP AND HUMIDITY:**

AM-C	25.2 ft <sup>3</sup> (714 liters)	35 to 70 °C	10-96%	±0.3 °C ±3.0% RH	208-230 / 1 / 30	34 x 28.5 x 45 in. (87 x 73 x 114 cm)	41 x 34.5 x 76.5 in. (104 x 88 x 194 cm)	4/14	500/227
CDM-C		2 to 70 °C	10-96%						720/327

**LOW TEMPERATURE:**

C-C-LT	25.2 ft <sup>3</sup> (714 liters)	-30 to 70 °C	N/A	±0.3 °C	208-230 / 1 / 30	34 x 28.5 x 45 in. (87 x 73 x 114 cm)	41 x 34.5 x 76.5 in. (104 x 88 x 194 cm)	4/14	720/327
CDM-C-LT			10-96%	30.3 °C 33.0% RH					765/347

**LOW HUMIDITY:**

CDMD-C	25.2 ft <sup>3</sup> (714 liters)	2 to 70 °C	10-96%	±0.3 °C ±3.0% RH	208-230 / 1 / 30	34 x 28.5 x 45 in. (87 x 73 x 114 cm)	41 x 34.5 x 76.5 in. (104 x 88 x 194 cm)	4/14	750/340
CDM-C-AT		2 to 70 °C	10-96%						750/340